

Head and Face Protection

MEETS
ASTM F-1506-02A
AND CSA Z462
SPECIFICATIONS




4692

- Includes 12 cal/cm² faceshield with chin cup
- Slotted visor adapter
- Dielectric hard hat



4693

- Includes 12 cal/cm² faceshield with chin cup
- Universal visor adapter
- Dielectric hard hat



4656

- Replaceable 12 cal/cm² faceshield with protective chin cup
- Attaches to 4660 or 4665



4660

- Visor adapter for slotted hardhats
- Flip up adjustable positioning



4665

- Visor adapter for non-slotted hard hats
- Flip up adjustable positioning



AG40LENS

- 40 cal/cm² replacement lens for all 40 cal Steel Grip hoods.

Also available

- **AG25LENS** — 25 cal/cm²
- **AG50LENS** — 50 cal/cm²
- **AG65LENS** — 65 cal/cm²



CXK 2310

- Arc Rating 23 cal/cm² head area
- Arc Rating 12 cal/cm² neck area
- 2-ply stretch 7.4 oz. knit CarbonX® with 1-ply cape
- Full face opening



NK2310

- 2-ply stretch white NOMEX® hood with 1-ply cape
- Half face opening or full face opening available



H11RY

- Arc Rating 12 cal/cm².
- single layer of Ultra Soft®



KITHP12GGL

12 cal goggle/balaclava combination

- Arc rating (ATPV) of 12 cal/cm² when used in combination
- Provides increased flexibility with excellent breathability



H62RK & H08GGL

27 cal goggle/balaclava combination

- Arc rating 27 cal/cm² when used together
- double layer balaclava made from knit material of Carbon and Kevlar® fiber



H49CX & H10GGLN

45 cal goggle/balaclava combination

- Arc rating 45.8 cal/cm² when used in combination
- triple layer balaclava made from knit material of Carbon X